



### Specifications

Operating Weight(kg)	34000
Engine Power(kW/rpm)	197/1950
Standard Bucket Capacity(m <sup>3</sup> )	1.6
Standard Bucket Width (with side cutters)(mm)	1460

### Performance

Travel Speed(Low/High) (km/h)	3.25/5.43
Swing Speed (rpm)	9.5
Ground Pressure (kPa)	68
Gradeability(°)	35
Maximum Arm Crowd Force(kN)	155.13/168.6
Maximum Bucket Digging Force(kN)	181.1/197

### Equipments

Engine Model	Cummins C8.3 -C
Displacement(L)	8.3
Swing Device Driving Type	Hydraulic Drive
Travel Device Driving Type	Hydraulic Drive
Brake Type	Hydraulic Lock
Standard Track Shoe Type	Triple Grouser shoes
Track Adjustment Device	Grease Tension
Hydraulic Pump Type	Variable Piston Pump
Maximum Setting Pressure	Traveling (MPa) 34.3
	Working (MPa) 34.3

### Implement

Boom Length (mm)	6470
Arm Length (mm)	2900
Bucket Radius(mm)	R1670

### Refill Capacity

Fuel (diesel)(L)	580
Hydraulic oil (Refilling)(L)	220/300
Battery Capacity	2×120AH



#### New Industry Standard

Intelligent Measure Control Service System allows intuitive interaction between the user and the machine. It features **LED display, intuitive user interface, maintenance alarm system.**



#### Breakthrough in Power Management

**Optimal Engine Management System** swiftly coordinates the engine and its peripherals, enabling the machine to function at its best with **minimal fuel consumption.**



#### Comprehensive Working Structures

Multidirectional application of new design concepts, coupled with previous expertise creates new industry breakthrough on durability, performance and operation diversity.



#### New Safety Standard

Eco-friendly 360°Protective Structure enhances the durability of the Cab. Features **Quick Defrost, Air Conditioner, Built-in anti-noise acoustics** paired with an **Ergonomic Suspension Seat** with hydraulic shock absorber for fatigue free operations.

# LONKING

Efficiency Rules the Future

## CDM6365H HYDRAULIC EXCAVATOR

**Strong Structure, Heavy-load Mechanism**  
**Original Cummins Engine**  
**Easy Maintenance**



LONKING INTERNATIONAL STRATEGIC BUSINESS UNIT  
**LONKING HOLDINGS LIMITED**

Add:26 Minyi Road,Xinqiao,Songjiang Industrial Zone,Shanghai  
P.C: 201612

Tel: +86-21-37602205 / 37602211

Fax:+86-21-57687966-8436 <http://www.lonkinggroup.com>

E-mail:[export@lonking.cn](mailto:export@lonking.cn) [marketing@lonkinggroup.com](mailto:marketing@lonkinggroup.com)

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd. and may not be used without written permission.

Printed 3 /2012 China

For more information on Lonking products,  
please visit [www.lonkinggroup.com](http://www.lonkinggroup.com)

## CDM

Load Right  
Load More *Series*

OPERATING WEIGHT:	34000kg
ENGINE POWER:	197kW/1950rpm
BUCKET CAPACITY:	1.6m <sup>3</sup>
TRAVEL SPEED:	3.25/5.43km/h

Specifications and design are subject to change without prior notice.  
Machines shown may not include optional accessories.